



BESCHERMER
SHIELD FOR TIMELINE

Waterproof Adhesive D3

Product Code: SSW/D32021

Characteristics

Product is an specially designed aqueous polyvinyl acetate dispersion with cross linking properties and a lowered minimum film forming temperature. The special features are an excellent water resistance as D3 class according to EN 204, high bond strength and heat resistance according to WATT 91 and a good setting time.

The film is slightly opaque and tack-free, no discoloration on oak.




Applications

Product code SSW/D32021 is successfully used as a mono-component vinyl acetate adhesive. It has a medium viscosity and reactive groups. The dispersion exhibits a rapid increase in bond strength when being pressed at temperatures of approx. 20°C as well as higher temperatures between 50 and 100°C.


(Available in Open mouth 30Kg pack only, Spl. packing on request and MOQ basis.)



EASY OF APPLICATION: VERY SMOOTH



CAN JOIN WOOD TO WOOD



QUICK AND EFFECTIVE RESULTS ON MDF TO LAMINATES



IMPRESSIVE RESULTS IN HOT AND COLD PRESSING



GOOD RESULTS ACHIVED: PLYWOOD TO PLYWOOD PLYWOOD TO LMINATES

Industrial Safety and Environmental Protection

Not a hazardous substance within the meaning of the current Dangerous Substance Regulations (GefStoffV).

SCO- 39, Basement, Spring Field Colony Market, Sector 31, Faridabad, 121003 Haryana INDIA
Cont. No. +91 -129-4009352, 9871199007, 9716577142, 9717367311
Email: sswoodculture@gmail.com, Website: www.ssgroupindia.co.in